

3D, Sunflower Mini-Shaker



DESCRIPTION

“Sunflower” **3D** Mini-Shaker provides adjustable three-dimensional smooth rotation of the platform and is designed for mixing blood samples, for minigel staining and destaining, sample washing, blot hybridization reactions.

Mini-Shaker is a compact device with low energy consumption. The use of direct drive and brushless motor allows continuous mixing up to 7 days and ensures reliable, trouble-free operation for more than 2 years.

Non-slip, temperature resistant, silicone mat located on the shaker's platform provides stable position for vessels during shaking. The platform is suitable for placing a versatile dimpled PDM mat for different size tubes.

Mini-Shaker can be used in cold rooms or incubators, operating at ambient temperature range +4°C to +40°C.

Optional dimpled mat **PDM** prevents different size tubes from rolling around the platform.



SPECIFICATION

Speed control range	5-60 rpm
Fixed tilt angle	7°
Direct drive mechanism	+
Maximum continuous operation time	168 hrs
Maximum load	1 kg
Platform working area	215x215 mm
Overall dimensions (WxDxH)	235x235x140 mm (with platform)
Weight	1.2 kg
Input current/power consumption	12 V, 260 mA/3.1 W
External power supply	Input AC 100-240 V; 50/60 Hz; Output DC 12 V

CAT. NR.

	3D incl. standard platform Bio PP-4S & external power supply unit
BS-010151-AAG	230VAC 50/60Hz Euro plug
BS-010151-AAK	230VAC 50/60Hz UK plug
BS-010151-AAK	230VAC 50/60Hz AU plug
BS-010151-AAK	100VAC 50/60Hz US plug
BS-010151-AAK	120VAC 60Hz US plug
-----	Optional accessories
PDM	PDM, dimpled mat
BS-010151-AK	IQ OQ document
BS-010151-BK	PQ document
-----	Replacement parts

3D, Sunflower Mini-Shaker



BS-010125-AK

Bio PP-4S, detachable platform with
non-slip thermoresistant silicone mat