

PST-100HL, Plate Shaker-Thermostat



DESCRIPTION

Plate Thermo-Shakers are designed for shaking and thermostating 2 standard 96-well microplates.

A multisystem principle, used in design of the Thermo-Shaker, allows operating it as 3 independent devices:

- Incubator;
- Microplate shaker;
- Thermo-Shaker.

A distinctive feature of Biosan Plate Thermo-Shakers is the **patented by the company Two-Side Microplates Heating**, which allows to achieve full correspondence of the set and actual temperature in the microplate wells.

Thermo-shaker **PST-100HL** with the ability to stabilize the temperature up to 100 ° C is specially designed for the hybridization reactions.

Plate Shaker-Thermostat provides:

- Soft or intensive sample shaking
- Rotation speed regulation, stabilization and indication
- Even rotation amplitude throughout the Thermo-Shaker platform
- Required operation time setting and indication
- Automatic stopping of the platform movement after expiration of the set time
- Setting and indication of the required temperature on the platform

Application fields:

- Cytochemistry — for in situ reactions
- Immunochemistry — for immunofluorescent reactions
- Biochemistry — for enzyme and protein analysis
- Molecular biology — for micro array analysis

SPECIFICATION

Temperature setting range	+25°C ... +100°C
Temperature control range	+5°C above ambient ... +100°C
Temperature setting resolution	0.1°C
Temperature stability	±0.1°C
Temperature uniformity at +37°C	±0.2°C
Orbit	2 mm
Speed control range	250–1200 rpm (increment 10 rpm)
Digital time setting	1 min–96 hrs / non-stop (increment 1 min)
Display	LCD, 16 x 2 signs
Max. height of microtest plate	18 mm
Number of microtest plates	2



Heat up time PST-100HL



CAT. NR.

	PST-100HL incl. external power supply unit
BS-010142-AAI	230VAC 50/60Hz Euro plug
BS-010142-AAQ	230VAC 50/60Hz UK plug
BS-010142-AA4	230VAC 50/60Hz AU plug
BS-010142-AAJ	100VAC 50/60Hz US plug
BS-010142-AAJ	120VAC 60Hz US plug

BS-010142-AK	IQ OQ document
BS-010142-BK	PQ document

PST-100HL, Plate Shaker-Thermostat



Patented two-side microplate heating +

Weight	5.9 kg
--------	--------

Platform dimensions (w x d)	250 x 150 mm
-----------------------------	--------------

Overall dimensions (WxDxH)	270 x 260 x 125 mm
----------------------------	--------------------

Input current/power consumption	12 V, 5 A / 60 W
---------------------------------	------------------

External power supply	Input AC 100-240 V; 50/60 Hz; Output DC 12 V
-----------------------	---